



## Kabelbinder aus Polyamid 6.6



### Zugfestigkeit nach Breite

2.5mm Wide Cable Ties : 8.1 kg (18lbs)  
 3.6mm Wide Cable Ties : 18.2 kg (40lbs)  
 4.8mm Wide Cable Ties : 22.2 kg (50lbs)  
 7.6mm Wide Cable Ties : 54.4 kg (120lbs)  
 9.0mm Wide Cable Ties : 79.4 kg (175lbs)  
 13,0mm Wide Cable Ties : 114.0 kg (250lbs)

### Spezifikation

Material Nylon PA6.6  
 Entflammbarkeit UL94-V2  
 Temperatur: -40°C bis +85°C  
 Halogenfrei / Raucharm

Artikel	Abmessung	Karton	VPE	Max. Bündel	Zugfestigkeit
BT8025(B)	80 x 2,5 mm	70.000	100	15 mm	8 kg
BT10025(B)	100 x 2,5 mm	55.000	100/1000	22 mm	8 kg
BT16025(B)	160 x 2,5 mm	40.000	100/1000	43 mm	8 kg
BT20025(B)	200 x 2,5 mm	30.000	100/1000	50 mm	8 kg
BT14036(B)	140 x 3,6 mm	30.000	100/1000	33 mm	18 kg
BT20036(B)	200 x 3,6 mm	20.000	100/1000	50 mm	18 kg
BT30036(B)	300 x 3,6 mm	17.000	100	76 mm	18 kg
BT37036(B)	370 x 3,6 mm	12.000	100	102 mm	18 kg
BT12048(B)	120 x 4,8 mm	20.000	100	24 mm	22 kg
BT16048(B)	160 x 4,8 mm	16.000	100/1000	38 mm	22 kg
BT20048(B)	200 x 4,8 mm	16.000	100/1000	50 mm	22 kg
BT25048(B)	250 x 4,8 mm	12.000	100	65 mm	22 kg
BT30048(B)	300 x 4,8 mm	11.000	100	80 mm	22 kg
BT37048(B)	370 x 4,8 mm	9.000	100	102 mm	22 kg
BT43048(B)	430 x 4,8 mm	7.500	100	120 mm	22 kg
BT53048(B)	530 x 4,8 mm	5.600	100	150 mm	22 kg
BZ63048(B)	630 x 4,8 mm	5.000	100	190 mm	22 kg
BT73048(B)	730 x 4,8 mm	4.000	100	224 mm	22 kg

